

The AGuru Machinery yield-till® Row Unit:

One size does not fit all.

Integrated Crop Residue Management System

clean-cut™ row cleaner

- ▶ Front-side mounted row cleaner
- ▶ 17 inch spike wheels
- ▶ Twin race deep V ball bearings in welded hub
- ▶ Mounted to same axle as center couler

clean-cut™ center couler

- ▶ Large 24 inch couler, 18 inch depth band, 3 inch running depth
- ▶ Dual, twin race heavy bearings in welded hub

Integrated Soil Tilth System

strip-keeper™ side coulers

- ▶ 15 inch, 18 inch, or 20 inch couler options
- ▶ Twin race heavy bearing in welded hub
- ▶ Simple adjust: loosen one bolt, turn the spiral for depth
- ▶ Tool-less adjust for width and angle
- ▶ Air over hydraulic shock down force

posi-depth™ shank/knife

- ▶ Tall shank, for plenty of soil flow clearance under the shank beam
- ▶ Shank: bolts into shank beam, including shear bolt
- ▶ Shear bolt is in hardened shear sleeve, that tightens against shank
- ▶ Integrated shank handle
- ▶ Fabricated and welded point
- ▶ Extra strong spring pack, dual springs



Heavy Duty and Super Duty Row Unit

Integrated Plant Food Availability – Precision Nutrient Placement System

root zone placement with couler tillage system

- ▶ Dry fertilizer tube places fertilizer forward between side tillage coulers, just behind center couler
- ▶ Liquid tube option

root zone band with shank/knife tillage system

- ▶ Dry fertilizer tube places fertilizer behind shank, 3” above point depth
- ▶ Liquid tube runs down back of shank

Integrated Seed Bed Conditions System

berm-builders

- ▶ 18 inch, or 20 inch couler options work with both shank and couler tillage configurations
- ▶ Twin race heavy bearing in welded hub
- ▶ Simple adjust for depth
- ▶ Tool-less adjust for width and angle
- ▶ Mounted to strip-conditioner arms
- ▶ Air over hydraulic shock down force

Spider gang strip-conditioner

- ▶ 4 – Super Duty and Heavy Duty – or 2 on Low Draft, reverse curved cast spider wheels
- ▶ Depth gauged at the gang, 12” - spring, 14” fall, depth gauge wheels
- ▶ Air over hydraulic shock down force

Strip Till. Better.

**AGURU
MACHINERY**